

LIQUID ROC 300

FOR BABA-DRIVEN PROJECTS
— ANCHORED IN AMERICA

LR300 is manufactured in the USA to help contractors and agencies meet today's Buy America/Build America expectations on DOT and federally funded projects. Stay bid-eligible, avoid waiver risk, and keep schedules on track.

Regulations changed. Lead times tightened. LR300 — Made in the USA — keeps your projects compliant, your submittals moving, and your crews working.

Switch to U.S.- Made LR300 for your DOT Projects — Request Pricing Today!



MKTfasteningUSA.com

501-676-2222 | info@MKTfasteningUSA.com
1 Gunnebo Drive · Lonoke, AR 72086



- Twin Tube – polyester resin base, benzoyl peroxide hardener
- Square cut rods – A307 steel, zinc plated. Other sizes, materials and finishes available upon request
- 9 month shelf life

BENEFITS:

- Pre-measured adhesive
- Easy to use and can be saved for re-use
- Nozzle included
- Can be used with screen tubes in hollow applications
- Works well in horizontal and non-structural overhead applications

CURE TIME

Concrete Temperature	Time
Over 80°F.	20-30 min.
80° to 68°F.	30-40 min.
68° to 58°F.	40-50 min.
58° to 48°F.	60 min.
48° to 38°F.	2 hrs.
38° to 28°F.	4 hrs.

APPLICATIONS AND INTENDED USE:

Used for Doweling in DOT road work applications and for pasting ports during crack repair.