

SUP-[®] SPLIT



AVAILABLE MATERIALS

- High strength, heat treated alloy steel, zinc plated
- Flat head
- Nickel rich electroplate for corrosive environments (1674120CR + 1674140CR)

FEATURES / ADVANTAGES

- Required hole diameter equals anchor diameter
- Friction set in solid masonry or stone
- High strength, heat treated alloy steel
- Corrosion resistant (CR) for use in harsh climates or with ACQ lumber

APPROVALS / LISTINGS

- G.S.A. Spec A-A-1925A, CID TYPE 2
- Contact customer service for approvals

CONSIDERATIONS

- Dead loads only

ORDER DETAIL

Ultimate Loads in lbs.							
Order Code	Size	Hole Dia	Tension (lbs.)	Shear (lbs.)	Minimum Embedment	Box Qty.	Master Qty.
1674060	1/4"x1-1/2"	1/4"	2,010	2,230	1-1/8"	100	800
1674080	1/4"x2"	1/4"	2,010	2,230	1-1/8"	100	800
1674100	1/4"x2-1/2"	1/4"	2,010	2,230	1-1/8"	100	800
1674120	1/4"x3"	1/4"	2,010	2,230	1-1/8"	100	800
1674120CR	1/4"x3"	1/4"	2,010	2,230	1-1/8"	100	800
1674140	1/4"x3-1/2"	1/4"	2,010	2,230	1-1/8"	100	800
1674140CR	1/4"x3-1/2"	1/4"	2,010	2,230	1-1/8"	100	800
1674160	1/4"x4"	1/4"	2,010	2,230	1-1/8"	100	800

*Tested in 3000 P.S.I. Concrete

INSTALLATION

- 1 Using a carbide bit, drill hole at least a 1/4" deeper than the anchor embedment.
- 2 Clean hole of debris.
- 3 To set, drive anchor into hole through item to be fastened.

