



**AVAILABLE MATERIALS**

- The head is a formed, steel stamping with or without machine screws or hanger bolt, zinc plated
- Combo heads available on most sizes

**FEATURES/ADVANTAGES**

- Light to medium loads under dead or variable conditions in a variety of hollow base materials
- Wings lock quickly and positively after insertion through the wall

**CONSIDERATIONS**

- Hollow construction only

**ORDER DETAIL**

Hanger Type					Heads Only			
Order Code	Screw Size	Hole Dia.	Box Qty.	Master Qty.	Order Code	Size	Box Qty.	Master Qty.
8320500	3/16" x 4"	1/2"	50	150	8307000	1/8"	100	1,200
8325500	3/16" x 5"	1/2"	50	150	8317000	3/16"	100	800
8340500	1/4" x 4"	1/4"	50	150	8337000	1/4"	100	500
8345500	1/4" x 5"	1/4"	50	100	8357000	5/16"	100	300
					8377000	3/8"	100	200
					8387000	1/2"	25	75


**ORDER DETAIL**

Order Code	Screw Size	Available Screw Type	Hole Diameter	Tension 1/2" Dry Wall	Box Qty.	Master Qty.
8303000 (#6)	1/8" x 2"	RM	3/8"	120	50	1500
8305000	1/8" x 3"	RM	3/8"	120	50	1500
8310000	1/8" x 4"	RM	3/8"	120	50	600
8313000 (#10)	3/16" x 2"	R	1/2"	135	50	600
8315000	3/16" x 3"	RM	1/2"	135	50	400
8320000	3/16" x 4"	RM	1/2"	135	50	400
8325000	3/16" x 5"	R	1/2"	135	50	250
8330000	3/16" x 6"	R	1/2"	135	50	250
8335000	1/4" x 3"	RM	11/16"	145	50	400
8340000	1/4" x 4"	RM	11/16"	145	50	250
8345000	1/4" x 5"	R	11/16"	145	50	250
8350000	1/4" x 6"	R	7/8"	145	50	250
8355000	5/16" x 3"	R	7/8"	160	50	250
8360000	5/16" x 4"	R	7/8"	160	50	150
8362000	5/16" x 5"	R	7/8"	160	50	150
8365000	5/16" x 6"	R	7/8"	160	50	150
8370000	3/8" x 3"	R	7/8"	160	50	150
8375000	3/8" x 4"	R	7/8"	160	50	150
8378000	3/8" x 5"	R	7/8"	160	50	100
8380000	3/8" x 6"	R	7/8"	160	50	100
8385000	1/2" x 4"	R	1-1/4"	185	25	50
8390000	1/2" x 6"	R	1-1/4"	185	25	50

R = Round Head, ex. 8315000  
M = Mushroom Head - 2 on order code, ex. 8315200

**INSTALLATION**

- 1 Drill recommended diameter hole through base material.
- 2 Clean hole of debris.
- 3 Insert bolt through fixture to be fastened, screw wing nut onto bolt.
- 4 Push wing through drilled hole.
- 5 Tighten screw.



**AVAILABLE MATERIALS**

- Polypropylene

**FEATURES/ADVANTAGES**

- Light loads only under dead or slightly variable conditions in all atmospheric conditions
- Accepts both wood and sheet metal screws
- Fast, easy installation

**ORDER DETAIL**

Order Code	Diameter & Length	Hole Dia.	Screw Size	Ultimate Tension in Lbs.* Screw Size Tested				Box Qty.	Master Qty.
				8 x 1-1/4"	10 x 1-1/4"	10 x 1-1/2"	12 x 1-1/2"		
8450000	3/16" x 7/8"	3/16"	8-10	115	385	—	—	100	3,000
8451000	3/16" x 7/8"	3/16"	8-10	115	385	—	—	1,000	5,000
8460000	1/4" x 1"	1/4"	10-12	—	—	195	543	100	3,000
8461000	1/4" x 1"	1/4"	10-12	—	—	195	543	1,000	3,000
8430000	5/16" x 1-3/8"	5/16"	14-16	n/a	n/a	n/a	n/a	100	1,200
Kits With Drill And Screws									
**8450100	3/16" x 7/8"	3/16"	8	115	385	—	—	1	12
**8460100	1/4" x 1"	1/4"	10	—	—	195	543	1	12

\*Tested in concrete block.  
\*\*Includes Carbide Drill Bit and 100 Anchors and Screws

**INSTALLATION**

- 1 Drill recommended diameter hole slightly deeper than length of anchor.
- 2 Clean hole of debris.
- 3 Insert plastic anchor into hole.
- 4 Place fixture over anchor and insert screw through fixture and into anchor.
- 5 Tighten screw.

